



# Doulton Triple Undersink featuring the Doulton Sterasyl

0.9 Micron Absolute Ceramic  
Advanced micro-biological protection

Premium Carbon Block  
Superior heavy metal removal

5 Year Warranty\*  
Hand built & tested in Australia



The Fluoride Triple Undersink combines ultra-fine ceramic, premium sub-micron carbon filtration and the Omnipure Fluoride Filter.

- The highly porous surface area of the Omnipure Fluoride Filter makes this cartridge ideal for the effective removal of Fluoride from your drinking water.

Exceptional cost to performance value.



**WaterMark Certificate No.: 23124**

The Australian WaterMark Standard Approval of this system is your guarantee of quality.


## Specifications

Item Code	IT003054
Filter Output	5,000 litres
Max Flow Rate	3 litres p/min
Dimensions (cm)	40(W) x 33(H) x 13(D)
Micron Rating	0.9 micron absolute
Warranty	5 years*

## Filtration Test Results

Impurities	% Reduction
Sediment/Dirt, Rust	>99.999
<b>Pathogenic Organisms:</b>	
e-Coli, Cholera, Shigella, Typhoid	>99.999
Cryptosporidium, Giardia	>99.999
<b>Trace Organics:</b>	
Volatile Organic Contaminants	>99.9
Pesticides & Herbicides	>99.9
Iron, Lead, Manganese, Cadium	>99.9
Zinc	>99.7
<b>Inorganics:</b>	
Residual Chlorine Content	>99.0
Fluoride	>97.6 - 99.0

## Filtration Process Diagram 1



For more information go to [www.livingwhole.com.au](http://www.livingwhole.com.au)

\*Warranty Terms & Conditions apply.

# Fluoride Triple Undersink

## STAGE 1 The Doulton Sterasyl® Ceramic Pre-Filter Cartridge

0.9 micron absolute Made in UK




• Mechanically filters out harmful bacteria and parasites.

Manufactured with Doulton Sterasyl® Ceramic to provide genuine sub-micron filtration. This stage reduces fine particulate matter, bacteria, cysts and turbidity. Silver, incorporated within this ceramic structure provides enhanced bacteriostatic and self sterilizing properties.

Removes contaminants including:

Parasites	Salmonella
Cryptosporidium	Cholera
Giardia	Sediment
Shigella	Dirt
e-Coli	Rust



• The ceramic pre-filter protects the carbon block post filter cartridge, allowing it to function more effectively and last longer.



The Doulton Sterasyl® cartridge can be washed and reused

If the flow rate slows, simply scrub clean under cold, running water with a clean sponge or brush\*.

## STAGE 2 The Omnipure Fluoride Filter

1 micron Made in USA


The Omnipure Fluoride Filter contains fine-mesh Activated Alumina to effectively remove fluoride from the water supply by up to 99.9%. By the process of selective adsorption, a physical/chemical reaction takes place whereby the fluoride ions are removed from the water supply by binding to the media's oxidised surface.

Removes contaminants including:

Up to 99.0% Fluoride Reduction

• The highly porous media of the Omnipure Fluoride cartridge has a optimal surface area of 200m<sup>2</sup> per gram for premium filtration efficiency.

• EPA listed media



\*We recommend replacing your Doulton Sterasyl® Ceramic cartridge every 2 years and Carbon Block post-filter yearly.

## STAGE 3 Premium Carbon Block Post-Filter


1 micron Made in USA

The 1 micron carbon block filter effectively removes chlorine, heavy metals and the unpleasant tastes and odour associated with these contaminants.


Removes contaminants including:

Chlorine	Lead
Aluminium	Mercury
Cadmium	Zinc
Copper	Odour
Manganese	Taste

• Made from premium coconut-shell carbon - fresher, sweeter tasting water is ensured.



## System Assembly Diagram 2



For Installation and Maintenance assistance please contact on 07 5391 3866.

### Labelled Components

- A** Doulton Ceramic Sterasyl® Pre- Made in UK
- B** Filter The Omnipure Fluoride Filter Made in USA
- C** Premium Carbon Block Post Filter Made in USA
- 1** Housing Sump
- 2** Housing Cap
- 3** Stainless Steel Bracket
- 4** Pressure Limiting Valve (PLV)
- 5** John Guest Elbow (with red clips)

### Available plumbing options

We stock a large range of brass plumbing parts and John Guest Speedfit® fittings for your plumbing requirements. All fittings include a Pressure Limiting Valve.



1/2" Female/Male Tee



3/4" Male Female Dishwasher



1/2" Male/Male Tee